Continental

Refrigerator

72" FRONT BREATHER SANDWICH UNIT REFRIGERATORS



3W/2-10-FB

Models Available

- SW72-12-FB SW72-12C-FB SW72-18M-FB
- SW72-18-FB SW72-18C-FB SW72-27M-FB
 - SW72-30M-FB

Utilizing Environmentally Safe, CFC-free R-134a Refrigerant



Standard Features

- Unique Air Flow Distribution Allows Pan Product to Maintain 33°–41°F Being in Compliance with and Certified Under the '98 NSF Standard For Preparation Units.
- · Modern, State-of-the-Art Styling
- Performance Rated Refrigeration System Utilizing Environmentally Safe R-134a Refrigerant
- · Easily Serviceable Back Mounted Compressor
- 2" Non-CFC Polyurethane Foam Insulation
- · Spring Loaded, Self Closing Door
- · Magnetic Snap-In Gasket
- 35/8" Casters, two with brakes, two without brakes
- · Heavy-Duty, Epoxy-Coated Steel Shelves
- Interior Hanging Thermometer
- · Full Length Nylon Cutting Board
- Cabinet Construction Consisting of Stainless Steel Front and Top, Aluminum End Panels, Case Back and Interior
- · Non-Corrosive, Plasticized Fin Evaporator Coil
- · Completely Enclosed, Vented and Removable Case Back
- Automatic, Energy Saving, Non-Electric Condensate Disposal
- 1/6 Size Pans, 4" Deep
- · 10 ft Cord and Plug Attached

Optional Features & Accessories

- · Electric Condensate
- Pan Opening Sizes
- Stainless Steel End Panels-SA Models
- Stainless Steel Interior & Exterior-SS Models
- Stainless Steel Finished Back in Lieu of Aluminum
- · Remote Models R
- · Additional Shelves
- · Door Locks
- · Single Overshelf
- · Double Overself
- Drawers

72" FRONT BREATHER SANDWICH UNIT REFRIGERATORS

| SPECIFICATIONS | SW72-12-FB | SW72-18-FB | SW72-12C-FB | SW72-18C-FB | SW72-18M-FB | SW72-27M-FB | SW72-30M-FB |
|--|---------------------------------------|---------------------------------------|---|--|---------------------------------------|---|---------------------------------------|
| DIMENSIONAL DATA | | | | | | | |
| Net Capacity (cu. ft.) | 20.6 | 20.6 | 20.6 | 20.6 | 20.6 | 20.6 | 20.6 |
| ¹ / ₆ Size Pans | 12 | 18 | 12 | 18 | 18 | 27 | 30 |
| Width, Overall (in.) | 72 | 72 | 72 | 72 | 72 | 72 | 72 |
| Depth, (incl. Hdls.& Bumpers) (in.) | 31 | 31 | 31 | 31 | 31 | 31 | 31 |
| Depth, Body Only (Less Door(s)(in.) | 27 ¹ / ₂ | 27 ¹ / ₂ | 27 ¹ / ₂ | 27 ¹ / ₂ | 27 ¹ / ₂ | 27 ¹ / ₂ | 27 ¹ / ₂ |
| Depth, Cutting Board | 12 | 12 | 19 | 19 | 10 | 10 | 10 |
| Height, Overall (incl. 35/k" Casters) (in.) | 40 7/8 | 40 7/8 | 40 7/8 | 40 7/8 | 40 7/8 | 40 7/8 | 40 7/8 |
| Shelf Area (sq. ft.) | 10.2 | 10.2 | 10.2 | 10.2 | 10.2 | 10.2 | 10.2 |
| No. of Shelves | 3 | 3 | 3 | 3 | 3 | 3 | 3 |
| No. of Doors | 3 | 3 | 3 | 3 | 3 | 3 | 3 |
| Condensing Unit Size (H.P.) | 1/4 | 1/4 | 1/4 | 1/4 | 1/4 | 1/4 | 1/4 |
| Refrigerant | R134a | R134a | R134a | R134a | R134a | R134a | R134a |
| Cabinet Electrical | 115/60/1 | 115/60/1 | 115/60/1 | 115/60/1 | 115/60/1 | 115/60/1 | 115/60/1 |
| Amps | 9.0 | 9.0 | 9.0 | 9.0 | 9.0 | 9.0 | 9.0 |
| Fans | 4 | 4 | 4 | 4 | 4 | 4 | 4 |
| Interior Depth (in.) | 20 | 20 | 20 | 20 | 20 | 20 | 20 |
| Interior Height (in.) | 26 ¹ / ₄ | 26 ¹ / ₄ | 26 ¹ / ₄ | 26 ¹ / ₄ | 26 ¹ / ₄ | 26 ¹ / ₄ | 26 ¹ / ₄ |
| Interior Width (in.) | 68 | 68 | 68 | 68 | 68 | 68 | 68 |
| Shipping Weight (lbs.) | 385 | 389 | 398 | 398 | 398 | 414 | 420 |
| Shipping Height (in.) | 431/4 | 431/4 | 431/4 | 431/4 | 431/4 | 431/4 | 431/4 |
| Shipping Length (in.) | 80 ¹ / ₄ | 80 ¹ / ₄ | 80 ¹ / ₄ | 80 ¹ / ₄ | 80 ¹ / ₄ | 80 ¹ / ₄ | 80 ¹ / ₄ |
| Shipping Depth (in.) | 46 | 46 | 46 | 46 | 46 | 46 | 46 |
| 72 19 1/16 DOOR OPENING 223 NA DOOR OPENING | 1938 | 40 7/8 441/16 | 187/8 1938 - 147/8 - DOOR OPENING 101/4 | 33 7/8 | 40 7/8 23 3/4 DOOR OPENING | 1938 ———————————————————————————————————— | 40.76 33.76 |
| | 35/8 | | 101/4 | | <u> </u> | | 35/8 |
| FRONT VIEW | Standard Top Side | View | C -Top | Side View | | M -Top Side Viev | 1 1 |
| 72" | 72" | - | - | 72 | - | 72 — | - |
| 24" | | | T | 24- | T | | |
| 30" | | | 34 | | 34 | | # ₩ |
| | | | | 19 | | | 19 |
| 12" | | | <u>+</u> | ······································ | <u> </u> | | |
| SW72-12 | SW72-18 | | T 3 1/4 SW7 | 72-12C | 1 | SW72-18C | 4 |
| | | | | | 3 1/4 | | |
| 72 | | | | | | | |
| -24- | | 72 — | - | - | 72 — | - | |
| 1 | 1 | | | 1 | | | |
| | 34 | ++++- | | 34 | | | |
| 34 | | | 。 10 | 34 <u> </u> | | <u> </u> | |
| ° 10 | | | | <u> </u> | | ° 10 | |
| SW72-18M | | SW72-27 | T M | | SW72-30N | Л | |
| | | | | | | | |

